

ELITE RANGE CAMERA



Compact flush mount camera

BE-300C - Left side-view (low mount)	2052
BE-301C - Right side-view (low mount)	2053
BE-302C - Rear view (high mount)	2065
BE-303C - Front or side-view (high mount)	2091
BE-304C - Internal view (ceiling mount)	2092

• **Viewing angle (HxVxD)**
95 x 72 x 125°

• **IP68**

• **Size (WxHxD)**
50 x 45 x 65mm

• **3 year warranty**



Features

- Mirror view (except BE-303C)
- 1/3" Sony CCD
- TV System: PAL
- TV Lines: 420

Power

- Power consumption: 1.2 Watts
- Current: 0.1 Amps

Durability & Standards

- Mechanical vibration: 20G
- Mechanical shock: 100G
- Operating temperature: -30 to +80°C
- CE marked
- EMC approved: e
- Approved for indirect vision
- HALT tested

ELITE RANGE CAMERA



MD-50 - Mini dome camera (internal use)

2581

• **Viewing angle (HxVxD)**
79 x 69 x 94°

• **IP66**

• **Size (Diameter x H)**
76 x 26mm

• **3 year warranty**



Features

- 1/3" CCD
- TV System: PAL
- TV Lines: 330

Durability & Standards

- Mechanical vibration: 5G
- Mechanical shock: 100G
- Operating temperature: -10 to +55°C
- CE marked

OPTIONAL EXTRAS



MD-50SM - Surface mounting adapter (20mm deep)

2582

MD-50AM - Angled surface mounting adapter (adds 15°)

2583